



SERIE **022S** ■

PNEUMATIC COUPLINGS
PNEUMATISCHE KUPPLUNGEN



SAFETY SELF VENTING TYPE **SICHEREITSVERRIEGELUNG**

Interchangeability - Kompatibilität
TST 014 & 022, ARO 210, RECTUS 14 & 22,
Industrial Interchange 1/4", Orion 44510,
CEJN 300, JWL 522 & 532, DynaQuip DM-2,
Aerequip FD41, Gromelle G-16600

Temperature Range - Temperaturbereich
-20 °C +100 °C (-4 °F +212 °F)



Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508 PSI)

Flow capacity - Nennweite
NW - 5.5


For optional orders please add the symbol
of your option end of the order no.
Bei Bestellungen Kennbuchstabe
bitte hinzufügen.

Material - Material


- Coupler Body - Kupplungsgrundkörper : Brass Nickel Plated - Messing Vernickelt
- Back Part - Hinterteil : Brass Nickel Plated - Messing vernickelt
- Sleeve - Hülse : Plastic - Kunststoff
- Valve - Ventil : Brass - Messing
- Springs - Federn : Stainless Steel - Edelstahl
- Locking O-Ring - Sprengring : Steel Hardened & Zink Plated - Stahl Gehärtet und verzinkt
- Pins - Stifte : Stainless Steel - Edelstahl AISI 302
- Balls - Kugeln : AISI 420 Hardened - Edelstahl AISI 420
- Seals - Dichtungen : Nitrile (Ni) - NBR
- Plug - Nippel : (Recommended) Steel Hardened Nickel Plated - (Empfohlen) Stahl Gehärtet vernickelt




Couplers and Plugs
Kupplungen und Nippel



Male Thread Coupling
Kupplung mit Aussengewinde



Female Thread Coupling
Kupplung mit Innengewinde



Standard Hose Barb Coupling
Kupplung mit Schlauchtülle

Connection Anschlüsse	Order No Bestellnr.	SW	L	ØD
BSPT 1/4"	022 RGS 13	21	59,5	30
BSPT 3/8"	022 RGS 17	21	61	30
BSPT 1/2"	022 RGS 21	24	65	30
NPT 1/4"	022 TGS 13	21	59,5	30
NPT 3/8"	022 TGS 17	21	61	30
NPT 1/2"	022 TGS 21	24	65	30

BSP 1/4"	022 DGS 13	20	57,5	30
BSP 3/8"	022 DGS 17	20	57,5	30
BSP 1/2"	022 DGS 21	22	59,5	30
NPT 1/4"	022 NGS 13	21	63	30
NPT 3/8"	022 NGS 17	21	64	30
NPT 1/2"	022 NGS 21	24	67	30

Ø 6 - 1/4"	022 HGS 06	21	72	30
Ø 8 - 5/16"	022 HGS 08	21	72	30
Ø 10 - 3/8"	022 HGS 10	21	72	30
Ø 13 - 1/2"	022 HGS 13	21	72	30