



SERIE 032 ■

PNEUMATIC COUPLINGS
PNEUMATISCHE KUPPLUNGEN



Interchangeability - Kompatibilität
RECTUS 32KA, TEMA 1800

Temperature Range - Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508 PSI)

Flow capacity - Nennweite
NW - 10



Options - Optionen

- F - Straight through flow - ungehinderter Durchfluss
- S - Stainless Steel - Edelstahl
- V - FPM Seal - FKM Dichtung
- E - EPDM Seal - EPDM Dichtung


For optional orders please add the symbol of your option end of the order no.
Bei Optionsbestellungen Kennbuchstabe bitte hinzufügen (Beispiel: 032 RG 13-K-V)

Material - Material


- Coupler Body - Kupplungsgrundkörper: Brass Nickel Plated - Messing vernickelt
- Back Part - Hinterteil: Brass Nickel Plated - Messing vernickelt
- Sleeve - Hülse: Steel Nickel Plated - Stahl vernickelt
- Valve - Ventil: Messing Diecasting
- Springs - Federn: Stainless Steel - Edelstahl
- Balls - Kugeln: Stainless Steel - Edelstahl AISI 420
- Seals - Dichtungen: Nitrile (Ni) - NBR (Ni)
- Plug - Nippel: Steel Nickel Plated - Stahl vernickelt




Couplers and Plugs
Kupplungen und Nippel




Male Threaded Coupling
Kupplung mit Aussengewinde




Female Thread Coupling
Kupplung mit Innengewinde




Standard Hose Barb Coupling
Kupplung mit Schlauchtülle



Standard Hose Barb Plug
Nippel mit Schlauchtülle



Male Threaded Plug
Nippel mit Aussengewinde



Female Thread Plug
Nippel mit Innengewinde

Connection Anschlüsse	Order No Bestellnr.	SW	L	ØD
BSPT 1/4"	032 RG 13	24	61,4	27
BSPT 3/8"	032 RG 17	24	61,4	27
BSPT 1/2"	032 RG 21	24	61,4	27
BSPT 3/4"	032 RG 26	27	61,4	27

BSP 1/4"	032 DG 13	24	59	27
BSP 3/8"	032 DG 17	22	54,4	27
BSP 1/2"	032 DG 21	25	54,4	27

8 mm - 5/16"	032 HG 08	24	75	27
10 mm - 3/8"	032 HG 10	24	75	27
13 mm - 1/2"	032 HG 13	24	75	27
16 mm - 5/8"	032 HG 16	24	75	27
19 mm - 3/4"	032 HG 19	24	75	27


6 mm - 1/4"	032 HU 06		85	
8 mm - 5/16"	032 HU 08		85	
9 mm - 5/14"	032 HU 09		85	
10 mm - 3/8"	032 HU 10		85	
13 mm - 1/2"	032 HU 13		85	
16 mm - 5/8"	032 HU 16		85	
19 mm - 3/4"	032 HU 19		85	

BSPT 1/4"	032 RU 13	17	27	
BSPT 3/8"	032 RU 17	17	27	
BSPT 1/2"	032 RU 21	22	27	
BSPT 3/4"	032 RU 26	27	27	

BSP 1/4"	032 DU 13	17	36	
BSP 3/8"	032 DU 17	19	36	
BSP 1/2"	032 DU 21	25	40	

• **ONE HAND CONNECTION / EINKUPPELUNG MIT EINER HAND** •

For optional orders please add the symbol OH end of the order no.
Bei Bestellungen Kennbuchstabe OH hinzufügen



For only single shut-off sockets
Nur für den einseitig absperrende Kupplungen